prk-garage1.pdf **CONCRETE PAVER** 2 3/8" (60MM) MINIMUM THICKNESS **BEDDING SAND** APPROXIMATELY 1" TO 1 1/2" (25-40MM) **GEOTEXTILE TURNED UP AT SIDES** PROTECTION BOARD- 1/4" (7MM) MINIMUM THICKNESS **RIGID INSULATION- THICKNESS VARIES** WITH LOCAL CODES AND CLIMATE **SURFACE DRAIN** GASKET-HOLES FOR DRAINAGE WRAP W/ FILTER FABRIC WATERPROOF MEMBRANE

NOTES:

1. PROTECTION BOARD AND INSULATION MUST WITHSTAND STATIC AND DYNAMIC VEHICULAR LOADS.

Copyright 2018 Keystone Retaining Wall Systems, LLC The suitability and/or manner of use of any details contained in this document is the sole responsibility of the user. Final project specific designs shall be prepared by a licensed professional Engineer or Architect.



Minneapolis, MN 55435

952-897-1040

Designed By: RKM Checked By:

NO SCALE

Scale:

Title:

PARKING GARAGE OVER HABITABLE SPACE DRAIN Date: 03-2019

Revision:

KEYSTONE HARDSCAPES CONCRETE PAVER

Drawing No: 1 of 1