str-park-ex-asph-base1.pdf ADJACENT WALK/ LANDSCAPE **CONCRETE CURB AND GUTTER** PER LOCAL STANDARDS **GEOTEXTILE TURNED UP AT SIDES CONCRETE PAVER** 3 1/8" (80MM) MINIMUM THICKNESS **BEDDING SAND** APPROXIMATELY 1" TO 1 1/2" (25-40MM) **EXISTING ASPHALT PAVEMENT GEOTEXTILE ON ASPHALT EXISTING BASE EXISTING SOIL SUBGRADE** 2" (50MM) DRAIN PIPE/HOLE FILL W/PEA GRAVEL **COVER W/GEOTEXTILE** LOCATE AT LOWEST ELEVATIONS Copyright 2018 Keystone Retaining Wall Systems, LLC Designed By: Title: Date: STREET/ PARKING LOT The suitability and/or manner of use of any RKM 03-2019 details contained in this document is the sole OVERLAY ON EXISTING ASPHALT PAVEMENT responsibility of the user. Checked By: Revision: Final project specific designs shall be prepared by a licensed professional Engineer or Architect. Project: 4444 W 78th Street KEYSTONE HARDSCAPES CONCRETE PAVER Drawing No: Scale: Minneapolis, MN 55435 NO SCALE 1 of 1 952-897-1040