sw-conc-base1.pdf **CONCRETE CURB GEOTEXTILE TURNED UP AT SIDES CONCRETE PAVER** 2 3/8" (60MM) MINIMUM THICKNESS **BEDDING SAND** APPROXIMATELY 1" TO 1 1/2" (25-40MM) **CONCRETE SLAB** 4" (100MM) MINIMUM THICKNESS **COMPACTED SOIL SUBGRADE** 3" (75MM) O.D. PVC PIPE FILLED WITH PEA GRAVEL/ GEOTEXTILE WRAP ON TOP AND BOTTOM OF PIPE/ @ 36" (915MM) O.C. EXTEND 6" TO 12" (150-300MM) BELOW SUB-BASE.

Copyright 2018 Keystone Retaining Wall Systems, LLC
The suitability and/or manner of use of any
details contained in this document is the sole
responsibility of the user.

Final project specific designs shall be prepared by a licensed professional Engineer or Architect.



4444 W 78th Street Minneapolis, MN 55435 952-897-1040 Designed By: RKM

Checked By:

NO SCALE

Scale:

Title:

SIDEWALK / PLAZA ON CONCRETE BASE Date: 03-2019

Revision:

Project:

KEYSTONE HARDSCAPES CONCRETE PAVER

Drawing No: 1 of 1